



204

4500m +

Heavy Telescopic Double

Mast
Hodqson
Telescopic Double
Static Hook Load: 221,000 daN
Racking: + 4800m w/ (101.6 mm / 4 ")

Substructure
Hodqson
One Piece Step Down w/ Hyd Pony Subs
Setback Capacity: 178,000 daN
Casing Capacity: 150,000 daN
KB to Ground: 4.86 m
Clear Working Hight: 4.6 m

Drawworks
Riqmaster (800 hp / 600 kW) 5 speed
Input: Cummins (550 hp / 633 kW)

Mud Pump #1 (Triplex)
Emsco F-1300
Rated: 1350 hp / 1006 kW
Input: Cummins 1350 hp / 1006 kW

Mud Pump #2 (Triplex)
Emsco F-1300
Rated: 1350 hp / 1006 kW
Input: Cummins 1350 hp / 1006 kW

Mud System
Circulation System: 34.5 MPa / 5000 psi
1 Tank w/ 5 Compartments: 77.5 m3
Shakers: (2) Monqoose

Top Drive
Tesco HMI-250
Rating: 223,000 daN

Catwalk
Fully Automated Hyd RIII w/ Manifold PLC

Traveling Assembly
Block: Ideco 250T
Rated: 196,000 daN
Swivel: Interqrated with Top Drive

Rotary Table
National C-175 (444 mm / 17.5 ")

Generator / Light Plant
Rated: 650 hp / 485 kW
Input: Cummons (650 hp / 485 kW)
Rated: 650 hp / 485 kW
Input: Cummons (650 hp / 485 kW)

Well Control
BOP: (2) Townsend T81 Single Gate
- (279 mm / 11 ") - (21 Mpa / 3000 psi)
Choke manifold : (21 Mpa / 3000 psi)
- Size 79mm
Accumulator : 5 Station (416 L / 110 G) Wireless
Mud Gas Separator : (762 mm / 30 ")

Boiler
Saskatoon (125hp)

Tubulars
Drill Pipe: 101.6 mm / 4 " FH - 360JT
Drill Collars: 159mm / 6.25 " XH -18JT
Drill Collars: 203mm / 8 " XH - 3JT

